

303 Fabric Guard Application Instructions

Protect fabric from ultraviolet light and restore water repellency.

303 FABRIC GUARD FEATURES

- Excellent water and oil repellency
- Superior stain resistance & soil release characteristics
- Controls fading and resists mildew formation
- Does not alter color, feel, or breathability of fabric
- Environmentally safe (no ozone depleting solvents)
- Non-toxic and odorless when dry

APPLICATION

303 Fabric Guard is best applied in two light applications instead of one heavy dose. Choose a warm day (50-105°F) and spray in a well ventilated area. Avoid heat, sparks, smoking, or open flame during application (303 Fabric Guard is flammable until dry). Also avoid contact with skin and eyes (protective clothing is recommended).

Before application, test the colorfastness of the material or carpet by spraying in an inconspicuous area and wiping the area while wet to see if the color transfers. Clean material to be treated and let dry completely before applying 303 Fabric Guard. Spray evenly holding the nozzle tip 8 to 12 inches from the material. Only mist the exposed side of your material. **DO NOT SATURATE!** Allow the solvent to evaporate between applications. On fabrics the final application should dry and cure for 8 to 12 hours. When used on carpeting, a 12 to 24 hour drying period is best.

Avoid getting over-spray on wood finishes, vinyl, plastics and metals. Any over-spray should be wiped up immediately with a dry absorbent cloth.

Tips for New Fabric: During the fabrication process the factory finish can be worn causing the new fabric to “wet”, most commonly at the seams. To prevent or correct seam leaks, treat the seam with 303 High Tech Fabric Guard.



COVERAGE

A 16 oz. bottle of 303 Fabric Guard covers up to 100 square feet on most fabrics. A gallon covers up to 1000 square feet if applied with proper equipment (recommended use of a low volume air-less spray system equipped with even flat fan tip). Other applicators, such as paint sprayers and hand pumped garden sprayers, can be used but coverage diminishes. Expect greater coverage on lighter weight fabrics and less on heavier fabrics and carpeting.

303 Fabric Guard is endorsed by Glen Raven Mills for use on Sunbrella fabric.



Sailrite Enterprises, Inc.
2390 East 100 South, Columbia City, IN 46725

Phone (800) 348-2769 / (260) 244-4647

Fax (260) 818-2005

Email info@sailrite.com

Sailrite.com

© 2015 Sailrite Enterprises, Inc.