

## Shroud Turnbuckle Cover Kit

Assembly Instructions (#6451A; 6452A; 6453A)

### KIT INCLUDES:

- Leather
- Velcro
- Leechline
- Thread

Place the loop or the hook side of the velcro along one long edge of the leather and approximately 1/8" above the bottom edge (the edge without the prepunched holes). Think of this as the "inside" of the cover.

The leather stretches some during sewing; so, begin sewing (use a straight stitch approximately 4mm long) across the bottom 1" edge of the velcro and, then, sew up the long outer edge of the velcro. Remember to keep the edge of the velcro 1/8" inside the edge of the leather.

Next sew the long inner edge of the velcro and, then, the top 1" edge.

Now sew the other half of the velcro on the opposite side of the leather (the "outside"). Follow the same sewing sequence as in the steps above with the velcro starting 1/8" above the bottom edge of the leather and aligned 1/8" inside the long edge of the leather.

Finally, thread the leech line through the prepunched holes, place the cover around the turnbuckle, tie the line, and close the velcro.



**Sailrite Enterprises, Inc.**  
2390 East 100 South, Columbia City, IN 46725

**Phone** (800) 348-2769 / (260) 244-4647

**Fax** (260) 818-2005

**Email** info@sailrite.com

**Sailrite.com**

© 2015 Sailrite Enterprises, Inc.