

FASTENER TOOL SELECTION GUIDE

| STEP 1: CHOOSE A FASTENER | | STEP 2: SELECT AN INSTALLATION TOOL (CHOOSE ONLY ONE TOOL PER FASTENER) | | | | OTHER INSTALLATION TOOLS <small>Mallet #68563 and rubber cutting block #378100 recommended for use with hole cutters and anvils</small> |
|--|--|--|-----------------------|---------------------------|---------------------------------------|--|
| | | STEP 3: CHOOSE DIE (LISTED BELOW) <i>Recommended for quicker, easier installation</i> | | | | |
| NAME | PART # | PRES-N-SNAP #109011 | SNAPRITE #104500 | W-1 HAND PRESS #121274 | | |
| DOT® Snap Fastener Button Silver 11/64" Barrel | #333777 | #931012* | — | #120742 | #100949 + #102235 or #25204 + #102235 | |
| DOT® Snap Fastener Button (colored), 3/16" Barrel | #333032 #333024 #333028 #333014 | #931012* | — | #120742 | #100949 + #102235 or #25204 + #102235 | |
| DOT® Snap Fastener Button Silver, 1/4" Barrel | #333010 | #931012* | — | #120742 | #100949 + #102235 or #25204 + #102235 | |
| DOT® Snap Fastener Button Silver 5/16" Barrel | #333012 | #931012* | — | #120742 | #100949 + #102235 or #25204 + #102235 | |
| DOT® Snap Fastener Normal Action Socket | #333050 | #931022* | #104232* | #120742 | #100949 or #25204 | |
| DOT® Snap Fastener Hard Action Socket | #333058 | #931022* | #104232* | #120742 | #100949 or #25204 | |
| DOT® Snap Fastener Standard Stud | #333100 | #931037* | #104235* + #103754 | #120742 | #100949 or #25204 | |
| DOT® Snap Fastener & Pull The Dot Eyelet 1/4" | #333555 | #931041* | #104226* | #120742 | #100949 + #102235 or #25204 + #102235 | |
| DOT® Snap & Pull The Dot Eyelet 5/16" | #333558 | #931041* | #104226* | #120742 | #100949 + #102235 or #25204 + #102235 | |
| DOT® Snap Fastener Screw Stud 3/8", 8-15 Self-Tap | #333105 | — | — | — | Phillips Screwdriver | |
| DOT® Snap Fastener Screw Stud 5/8", 8-15 Self-Tap | #333110 | — | — | — | Phillips Screwdriver | |
| 3/8" Machine Screw (10-32) | #333115 | — | — | — | Phillips Screwdriver | |
| 5/8" Machine Screw (10-32) | #333118 | — | — | — | Phillips Screwdriver | |
| 3/8" Machine Screw (8-32) | #333120 | — | — | — | Phillips Screwdriver | |
| 5/8" Machine Screw (8-32) | #333125 | — | — | — | Phillips Screwdriver | |
| DOT® Snap Fasteners Gypsy Stud 3/16" Barrel | #333130 | #100899 | — | — | #100949 + #102235 or #25204 + #102235 | |
| 3/4" Windshield Clip | #333135 | — | — | — | No Tool Needed | |
| 7/8" Windshield Clip | #333138 | — | — | — | No Tool Needed | |
| DOT® Lift The Dot 2 Prong Stud | #888005 | — | — | — | #100972 + #120445 | |
| DOT® Lift The Dot Washer | #888010 | — | — | — | Flathead Screwdriver | |
| DOT® Lift The Dot Socket (Standard Legs) | #888015 | — | — | — | #110012 or #100695 + #120445 | |
| DOT® Lift The Dot Socket (Extended Legs) | #888017 | — | — | — | #110012 (p173) or #100695 + #120445 | |
| DOT® Lift The Dot Backplate | #888020 | — | — | — | Flathead Screwdriver | |
| DOT® Lift The Dot Screw Stud 1/2" | #888025 | — | — | — | Wrench | |
| DOT® Lift The Dot Machine Screw Stud 3/8" | #888030 | — | — | — | Wrench | |
| DOT® Lift The Dot Machine Screw Stud 5/8" | #888035 | — | — | — | Wrench | |
| DOT® Pull The Dot (One Way) Snaps - Button | #555777 | #931012* | — | — | #100949 + #102235 or #25204 + #102235 | |
| DOT® Pull The Dot (One Way) Snap - Socket | #555050 | #586325 | #104232* | — | #100949 + #25204 | |
| DOT® Pull The Dot (One Way) Snap | #555100 | #931037* | #104235* | — | #100949 + #102235 or #25204 + #102235 | |
| DOT® Pull The Dot (One Way) Snap - Screw Stud 3/8" | #555105 | — | — | — | Phillips Screwdriver | |
| DOT® Common Sense Barrel Stud | #104803 | #104993 | — | — | — | |
| DOT® Common Sense Backplate For Barrel Stud | #104804 | #104993 | — | — | — | |
| DOT® Lift The Dot Eyelet-Type Base Stud | #888050 | #106397 | — | — | — | |

* Included with tool kit

** Only sold in kits, not individual sale

*** Loxx® is compatible with the German TENAX® version and it not compatible with the English TENAX® products.

Cloth-To-Cloth (C-C) | Cloth-To-Surface (C-S)

| STEP 1: CHOOSE A FASTENER | | STEP 2: SELECT AN INSTALLATION TOOL (CHOOSE ONLY ONE TOOL PER FASTENER) | | | OTHER INSTALLATION TOOLS <small>Mallet #68563 and rubber cutting block #378100 recommended for use with hole cutters and anvils</small> |
|---|---------|--|---------------------|---------------------------|--|
| | | STEP 3: CHOOSE DIE (LISTED BELOW) <i>Recommended for quicker, easier installation</i> | | | |
| NAME | PART # | PRES-N-SNAP #109011 | SNAPRITE #104500 | W-1 HAND PRESS #121274 | |
| DOT® Lift The Dot Long Eyelet-Type Base Stud | #888055 | #106397 | — | — | — |
| DOT® Lift The Dot Eyelet-Type Base Washer | #888060 | #106397 | — | — | — |
| DOT® Common Sense Fastener Eyelet | #777005 | — | — | — | #108001 or #100696 (sailrite.com) + #120445 |
| DOT® Common Sense Fastener Eyelet (Extended Legs) | #777006 | — | — | — | #108001 or #100696 (sailrite.com) + #120445 |
| DOT® Common Sense Washer | #777010 | — | — | — | Flathead Screwdriver |
| DOT® Common Sense 2 Prong Stud | #777015 | — | — | — | #100972 + #120445 |
| DOT® Common Sense Fastener Clinch Plate | #777020 | — | — | — | — |
| DOT® Common Sense Fastener 5/8" Screw Stud | #777025 | — | — | — | #120751 (174), #100135 or Wrench |
| DOT® Common Sense Fastener 2 Screw Stud | #777030 | — | #104477 | — | #102235 or #104482 + #100949 (C-C) or #25204 (C-C) or Phillips Screwdriver (C-S) or #103543 (C-C) |
| DOT® Common Sense 2 Screw Stud Double High | #777035 | — | #104477 | — | #102235 or #104482 + #100949 (C-C) or #25204 (C-C) or Phillips Screwdriver (C-S) or #103543 (C-C) |
| Screw Flat Head 6 x 1/2" | #777040 | — | — | — | Phillips Screwdriver |
| DOT® Common Sense Oversized Washer | #777045 | — | — | — | No tool Needed |
| DOT® Common Sense Plastic Reinforced Washer | #777050 | — | — | — | No Tool Needed |
| Loxx® Pull It Up Fastener Upper Head with Regular Washer*** | #121356 | — | — | — | #18211 + #121357 or #121358 |
| Loxx® Pull It Up Fastener Upper Head with Long Washer*** | #121355 | — | — | — | #18211 + #121357 or #121358 |
| Loxx® Pull It Up Fastener Lower Stud with Regular Washer*** | #121349 | — | — | — | #18211 + #121357 or #121358 |
| Loxx® Pull It Up Fastener Lower Stud with Long Washer*** | #121348 | — | — | — | #18211 + #121357 or #121358 |
| Loxx® Pull It Up Fastener 5/8" Self-Tapping Screw Stud*** | #121353 | — | — | — | Wrench |
| Loxx® Pull It Up Fastener 1/2" Self-Tapping Screw Stud*** | #121354 | — | — | — | Wrench |
| Loxx® Pull It Up Fastener 1-3/8" Oval Plate Stud*** | #121350 | — | — | — | Screwdriver |
| Loxx® Pull It Up Fastener 1" Oval Plate Stud*** | #121351 | — | — | — | Screwdriver |
| Loxx® Pull It Up Fastener 3/8" Machine Screw Stud*** | #121352 | — | — | — | Wrench |
| Nut Stainless Steel*** | #121360 | — | — | — | Wrench |
| DOT® Lift The Dot Double Height Machine Screw Stud | #888075 | — | — | — | Wrench |
| DOT® Lift The Dot Double Height Stud Two Hole Base | #888070 | — | — | — | Screwdriver |
| Lift The Dot Fastener Standard Height Stud Two Hole Base | #888065 | — | — | — | Screwdriver |
| SnapRite® Snap Fastener Button Silver 11/64" Barrel | #104151 | #931012* | #104229* | — | #100949 + #102235 or #25204 + #102235 |
| SnapRite® Snap Fastener Button Silver 1/4" Barrel | #104154 | #931012* | #104229* | — | #100949 + #102235 or #25204 + #102235 |
| SnapRite® Snap Fastener Button Silver 11/64" Barrel | #104151 | #931012* | #104229* | — | #100949 + #102235 or #25204 + #102235 |
| SnapRite® Snap Fastener Button Silver 5/32" Barrel | #104153 | #931012* | #104229* | — | #100949 + #102235 |
| SnapRite® Snap Fastener Button Silver 1/4" Barrel | #444004 | #931012* | #104229* | — | #100949 + #102235 |
| SnapRite® Gypsy Stud 3/16" Barrel | #104236 | #100899 | #104235* | — | #100949 + #102235 or #25204 + #102235 |
| SnapRite® Pull The Dot (One Way) Snap Button 1/4" Barrel | #104299 | #931012* | #104229* | — | #100949 + #102235 or #25204 + #102235 |
| DOT® Snap Fastener Button 11/64" | #444777 | #931012* | — | #120742 | #100949 + #102235 |
| DOT® Snap Fastener Button 1/4" Barrel | #444888 | #931012* | — | #120742 | #100949 + #102235 |
| DOT® Snap Fastener Normal Action Socket (Stainless) | #444050 | #931022* | #104232* | #120742 | #100949 |
| DOT® Snap Fastener Stud Cloth-to-Cloth (Stainless) | #444100 | #931037* | #104235* + #103754 | #120742 | #100949 |
| DOT® Snap Fastener Eyelet (Stainless) | #444555 | #931041* | #104226* | #120742 | #100949 + #102235 |

* Included with tool kit
 ** Only sold in kits, not individual sale
 *** Loxx® is compatible with the German TENAX® version and it not compatible with the English TENAX® products.

Cloth-To-Cloth (C-C) | Cloth-To-Surface (C-S)

| STEP 1: CHOOSE A FASTENER | | STEP 2: SELECT AN INSTALLATION TOOL (CHOOSE ONLY ONE TOOL PER FASTENER) | | | | OTHER INSTALLATION TOOLS <small>Mallet #68563 and rubber cutting block #378100 recommended for use with hole cutters and anvils</small> |
|--|---------------------------------|--|---------------------|---------------------------|--|--|
| | | STEP 3: CHOOSE DIE (LISTED BELOW) <i>Recommended for quicker, easier installation</i> | | | | |
| NAME | PART # | PRES-N-SNAP #109011 | SNAPRITE #104500 | W-1 HAND PRESS #121274 | | |
| DOT® Snap Fastener Screw Stud 3/8" (Stainless) | #444105 | — | — | — | Phillips Screwdriver | |
| DOT® Snap Fastener Screw Stud 5/8" (Stainless) | #444110 | — | — | — | Phillips Screwdriver | |
| Twist Lock Fastener Eyelet (Stainless)** | Kit #777600 or #777500 | — | — | — | #120445 or Flathead Screwdriver | |
| Twist Lock Fastener 2 Hole Base (Stainless)** | | — | #104477 | — | #102235 or #104482 + #100949 (C-C) or Phillips Screwdriver (C-S) or #103543 (C-C) | |
| Twist Lock Fastener Clinch Plate (Stainless)** | | — | — | — | — | |