


SAIL SHACKLES

A sail shackle secures around the bail of a sail slug or slide. It is used to attach the slug or slide to the sail. Most sail shackles are used with a grommet installed along the edge of the sail. Attaching your slug or slide with a sail shackle and a grommet is the strongest and most common attachment method.

STAINLESS SCREW SHACKLE.....	2
SCREW-ON PLASTIC SHACKLE.....	2
SNAP-IN PLASTIC SHACKLES.....	2
SHACKLE INSERTS.....	3

STAINLESS SCREW SHACKLE 3/4" L X 1/2" W


PART #100043



A LENGTH	3/4"
B LOA	1"
C WIDTH (CLOSED)	1/2"
D PIN DIA.	1/8"

STAINLESS HEAVY DUTY SCREW SHACKLE


3/4" L X 3/8" W PART #100049



A LENGTH	3/4"
B LOA	1-1/8"
C WIDTH (CLOSED)	3/8"
D PIN DIA.	1/8"

STAINLESS HEAVY DUTY SCREW SHACKLE


1-1/16" L X 3/8" W PART #100047



A LENGTH	1-1/16"
B LOA	1-7/16"
C WIDTH (CLOSED)	3/8"
D PIN DIA.	1/8"

SCREW-ON PLASTIC SHACKLE WIDE 5/8"


PART #24105



A LENGTH	5/8"
B LOA	1"
C WIDTH (CLOSED)	1/8"
D PIN DIA.	1/4"
E THICKNESS	3/8"

SCREW-ON PLASTIC SHACKLE 15/16"


PART #24106



A LENGTH	15/16"
B LOA	1-5/8"
C WIDTH (CLOSED)	5/16"
D PIN DIA.	5/16"

HEAVY DUTY SCREW-ON PLASTIC SHACKLE 1-1/8"


PART #137



A LENGTH	1-1/8"
B LOA	1-7/8"
C WIDTH (CLOSED)	1/4"
D PIN DIA.	5/16"

SCREW-ON PLASTIC SHACKLE 1-1/8"


PART #103037



A LENGTH	1-1/8"
B LOA	1-3/4"
C WIDTH (CLOSED)	1/4"
D PIN DIA.	5/16"

SNAP-IN PLASTIC SHACKLE 7/8"


PART #727100



A LENGTH	7/8"
B LOA	1-5/8"
C WIDTH (CLOSED)	1/4"
D PIN DIA.	5/16"

SNAP-IN PLASTIC SHACKLE 1-1/8"

PART #728100



A LENGTH	1-1/8"
B LOA	1-7/8"
C WIDTH (CLOSED)	5/16"
D PIN DIA.	5/16"

SHACKLE INSERT

PART #100042

FOR USE WITH 7/8" SHACKLE



SHACKLE INSERT

PART #100041

FOR USE WITH 3/4" SHACKLE

