



SAFETY DATA SHEET

Issue Date 1992 11 01

Revision Date 2016 05 11

Version 10.11

1. IDENTIFICATION

Product identifier

Product Name SAILKOTE AEROSOL US

Other means of identification

Product Code SKC8

Synonyms Mixture

Recommended use of the chemical and restrictions on use

Recommended Use Dry lubricant.
Aerosol.

Uses advised against

Details of the supplier of the safety data sheet

Manufacturer Address McGee Industries, Inc.
9 Crozerville Rd
P.O. Box 2425
Aston, PA 19014

E-mail address info@mclube.com

Emergency telephone number

Company Phone Number 1-800-262-5823 (Within US)
1-610-459-1890

Emergency Telephone CHEMTREC:
1-800-424-9300 (Within US)
1-703-527-3887 (Outside US)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This material is considered hazardous. This information is supplied under the OSHA Hazard Communication Standard (29 CFR 1910.1200), and is offered in good faith based on data available to us that we believe to be true and accurate.

Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed gas
Chronic aquatic toxicant	Category 1

Label elements

Emergency Overview

Danger

Hazard statements

H222: Extremely flammable aerosol.
H229: Pressurized container: May burst if heated
H304: May be fatal if swallowed and enters airways
H316: Causes mild skin irritation
H336: May cause drowsiness or dizziness
H410: Very toxic to aquatic life with long lasting effects



Vapors may travel considerable distances to ignition sources and flash back. Hazardous gases can be produced requiring respirator. Heating above 500°F (260°C) may cause formation of potentially toxic substances.

Appearance white translucent

Physical state Liquid

Odor Sweet ester odor

Precautionary Statements - Prevention

P201: Obtain special instructions before use
P202: Do not handle until all safety precautions have been read and understood
P210: Keep away from heat/sparks/open flames/hot surfaces — No smoking
P211: Do not spray on an open flame or other ignition source
P251: Pressurized container: Do not pierce or burn, even after use
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P264: Wash skin thoroughly after handling
P270: Do not eat, drink or smoke when using this product
P271: Use only outdoors or in a well-ventilated area
P280: Wear protective gloves and eye / face protection

Precautionary Statements - Response

P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing
P312: Call a POISON CENTER or doctor/ physician if you feel unwell
P332 + P313: If skin irritation occurs: Get medical advice/ attention
P337 + P313: If eye irritation persists: Get medical advice/attention
IF SWALLOWED: Immediately call a POISON CENTER or doctor
Do NOT induce vomiting

Precautionary Statements - Storage

P410 + P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P405: Store locked up

Precautionary Statements - Disposal

P501: Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other Information

Prolonged exposure may cause chronic effects. May be irritating to eyes, respiratory system and skin. Prolonged skin contact may defat skin and produce dermatitis. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Aspiration into lungs can produce severe lung damage. Do not smoke. Do not contaminate tobacco products. The thermal decomposition vapours of fluorinated polymers may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal Do not puncture or burn aerosol can, even after use When operating continuously for long periods, the aerosol container can become very cold. Care should be taken to avoid skin burns.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable

Mixture
Synonyms

Mixture.

Chemical nature

Fluoropolymer dispersion, Aerosol

Component Information:

Chemical Name	CAS No.	Weight-%	Classification GHS Hazard Codes (OSHA HCS)
Heptane (n-)	142-82-5	40.0-50.0	Skin Irrit. 2; (H315) STOT SE 3; (H336) Asp. Tox. 1; (H304) Aquatic Acute 1; (H400) Aquatic Chronic 1; (H410) Flam. Liq. 2; (H225)
n-Butyl acetate	123-86-4	10.0-20.0	(EUH066) STOT SE 3 (H336) Flam. Liq. 3 (H226)
Dimethyl ether	115-10-6	10.0-20.0	Flam. Gas 1 (H220) Press. Gas (H280)
Ethanol	64-17-5	10.0-20.0	Flam. Liq. 2 (H225)
Carbon dioxide	124-28-9	2.0-5.0	-
Propan-2-ol	67-63-0	1.0-5.0	Eye Irrit. 2, (H319) STOT SE 3, (H336) Flam. Liq. 2, (H225) [Asp. Tox. 2, (H305)]

The exact percentage (concentration) of composition has been withheld as a trade secret.

For the full text of the Classifications and Hazard Statements mentioned in this Section, see Section 16

Amounts listed are typical and do not represent a specification. Remaining components are proprietary, nonhazardous, and/or present at amounts below reportable limits.

4. FIRST AID MEASURES

Description of first aid measures
General advice

Use first aid treatment according to the nature of the injury. Never give anything by mouth to an unconscious person. When symptoms persist or in all cases of doubt, seek medical advice.

Eye contact

Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.

Skin contact

Wash skin with soap and water. Get medical attention if irritation develops and persists. Wash contaminated clothing before reuse.

Inhalation

Remove from exposure, lie down. Artificial respiration and/or oxygen may be necessary. If symptoms persist, call a physician.

Ingestion Never give anything by mouth to an unconscious person. Clean mouth with water. Do NOT induce vomiting without medical advice. Potential for aspiration if swallowed. Call a physician.

Self-protection of the first aider First aider: Pay attention to self-protection. Remove all sources of ignition. Use personal protection recommended in Section 8.

Most important symptoms and effects, both acute and delayed

Symptoms Drowsiness. Dizziness.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Water spray (fog). Carbon dioxide (CO₂). Foam. Dry chemical. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

May be ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Flash back possible over considerable distance. Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Hazardous combustion products

Carbon oxides. Fluorinated compounds.

Explosion data

Sensitivity to Mechanical Impact

None.

Sensitivity to Static Discharge

May be ignited by heat, sparks or flames. All equipment used when handling must be grounded. Use spark-resistant tools.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Use personal protection recommended in Section 8. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges. Extremely slippery when spilled.

Environmental precautions

Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later disposal.

Methods for cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal. Clean contaminated

surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Contents under pressure. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Do not smoke. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Use personal protection recommended in Section 8.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Protect from sunlight. Store at temperatures not exceeding 50 °C/ 122 °F. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials

Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Components with Workplace Control Parameters:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Heptane (n-) 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m ³	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 85 ppm TWA: 350 mg/m ³
n-Butyl acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m ³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m ³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³
Ethanol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³
Propan-2-ol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³

Appropriate engineering controls

Engineering Controls

Ensure adequate ventilation, especially in confined areas. As a general rule, at least 10 air changes per hour are recommended at the workplace. Explosion-proof equipment (for example fans, switches, and grounded ducts) should be used in mechanical ventilation systems. Showers. Eyewash stations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Avoid contact with eyes. Wear safety glasses with side shields (or goggles).

Skin and body protection

Avoid skin contact. Wear protective gloves and protective clothing.

Respiratory protection

Ensure adequate ventilation, especially in confined areas. In case of insufficient ventilation,

wear suitable respiratory equipment. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties: Properties Apply to Liquid (Less Propellant)

Physical state	Liquid	
Appearance	white translucent	
Color	white	
Odor	Sweet ester odor	
Odor threshold	No data available	
<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	
Melting point / Freezing point	No data available	
Boiling point / boiling range	78 - 149 °C / 173 - 301 °F	
Flash point	- 4 °C / 24 °F	Tag Closed Cup
Evaporation rate	< 1	(Butyl Acetate = 1)
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability limit:	10.7	(Vol % @ 100°F (38°C))
Lower flammability limit:	2.02	(Vol % @ 100°F (38°C))
Vapor pressure	2.0	@ 20 °C (kPa)
Vapor density	3.5	(Air = 1)
Relative density	0.78	g/ml @ 20°C
Water solubility	< 10%	
Solubility in other solvents	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	325 - 400 °C / 600 - 750 °F	
Kinematic viscosity	No data available	
Dynamic viscosity	No data available	
Explosive properties	Not applicable	
Oxidizing properties	No data available	
<u>Other Information</u>		
Softening point	No data available	
Molecular weight	No data available	
VOC Content (%)	<= 96.0 Wt % (<= 740 g/L)	
Density	6.47 lbs./gal. (780 kg/m ³)	
Bulk density	No data available	

10. STABILITY AND REACTIVITY

<u>Reactivity</u>	Stable
<u>Chemical stability</u>	Stable
<u>Stability</u>	Stable
<u>Possibility of Hazardous Reactions</u>	None under normal processing
<u>Hazardous polymerization</u>	Hazardous polymerization does not occur.
<u>Conditions to avoid</u>	Heat, flames and sparks. Take precautionary measures against static discharges. Decomposition temperature: 325-400°C / 600-750°F.

Incompatible materials Strong oxidizing agents.

Hazardous Decomposition Products Carbon oxides. Fluorinated compounds.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	The product itself has not been tested
Inhalation	May cause irritation. Aspiration into lungs can produce severe lung damage.
Eye contact	May cause irritation.
Skin contact	May cause irritation.
Ingestion	Not an expected route of exposure. May be harmful if swallowed. Potential for aspiration if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Heptane (n-) 142-82-5	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	= 103 g/m ³ (Rat) 4 h
n-Butyl acetate 123-86-4	= 12789 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
Dimethyl ether 115-10-6	-	-	= 308.5 mg/L (Rat) 4 h
Ethanol 64-17-5	= 15010 mg/kg (Rat)	= 20000 mg/kg (Rabbit)	= 124.7 mg/L (Rat) 4 h
Propan-2-ol 67-63-0	= 5840 mg/kg (Rat)	= 13900 mg/kg (Rabbit)	> 25000 mg/m ³ (Rat) 6 h vapour

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen. (Note: Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage).

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethanol 64-17-5	A3	Group 1	Known	X

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Chronic toxicity Prolonged exposure may cause chronic effects. Prolonged skin contact may defat the skin and produce dermatitis. Repeated or prolonged exposure may cause central nervous system damage. Aspiration may cause pulmonary edema and pneumonitis.

Aspiration hazard Risk of serious damage to the lungs by aspiration.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

Oral LD50	> 5000 mg/kg
Dermal LD50	> 5000 mg/kg
Gas LC50	> 20000 ppm
Mist LC50	> 5 mg/l
Vapor LC50	9.75 mg/l

12. ECOLOGICAL INFORMATION

Marine pollutant Yes.

Ecotoxicity Acute Aquatic Toxicity, Category 1; Acute Summation Method
Chronic Aquatic Toxicity, Category 1; Chronic Summation Method

Component Information:

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Heptane (n-) 142-82-5	4,338: 72 h Pseudokirchneriella subcapitata mg/L EL50	375.0: 96 h Cichlid fish mg/L LC50	10: 24 h Daphnia magna mg/L EC50
n-Butyl acetate 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	100: 96 h Lepomis macrochirus mg/L LC50 static 17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 62: 96 h Leuciscus idus mg/L LC50 static	72.8: 24 h Daphnia magna mg/L EC50
Ethanol 64-17-5	1000: 96 h Chlorella vulgaris mg/L EC50	12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static	9268 - 14221: 48 h Daphnia magna mg/L LC50 10800: 24 h Daphnia magna mg/L EC50 2: 48 h Daphnia magna mg/L EC50 Static
Propan-2-ol 67-63-0	1000: 96 h Desmodesmus subspicatus mg/L EC50 1000: 72 h Desmodesmus subspicatus mg/L EC50	9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96 h Pimephales promelas mg/L LC50 static 1400000: 96 h Lepomis macrochirus µg/L LC50	13299: 48 h Daphnia magna mg/L EC50

Persistence and degradability No information available.

Bioaccumulation No information available.

Mobility No information available.

Component Information:

Chemical Name	Partition coefficient
Heptane (n-) 142-82-5	4.66
n-Butyl acetate 123-86-4	1.81
Dimethyl ether 115-10-6	-0.18
Ethanol 64-17-5	-0.32
Propan-2-ol 67-63-0	0.05

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Pressurized container: Do not pierce or burn, even after use. Disposal should be in accordance with applicable regional, national and local laws and regulations.

Chemical Name	California Hazardous Waste Status
Heptane (n-) 142-82-5	Toxic Ignitable
n-Butyl acetate 123-86-4	Toxic
Ethanol 64-17-5	Toxic Ignitable
Propan-2-ol 67-63-0	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

Proper shipping name Consumer Commodity
Hazard Class LIMITED QUANTITY

ICAO (air)

Proper shipping name Consumer Commodity, 9, ID8000

IATA

Proper shipping name Consumer Commodity, 9, ID8000

IMDG

Proper shipping name Aerosols, 2.1, UN1950, Limited Quantity

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Propan-2-ol - 67-63-0	1.0

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Butyl acetate 123-86-4	5000 lb	-	-	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
n-Butyl acetate 123-86-4	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals: (Note: Ethyl alcohol is only a considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage)

Chemical Name	California Proposition 65
Ethanol - 64-17-5	Carcinogen Developmental

U.S. State Right-to-Know Regulations

This product contains substances regulated by state right-to-know regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Heptane (n-) 142-82-5	X	X	X
n-Butyl acetate 123-86-4	X	X	X
Dimethyl ether 115-10-6	X	X	X
Ethanol 64-17-5	X	X	X
Propan-2-ol 67-63-0	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<u>NFPA</u>	Health hazards 2	Flammability 3	Instability 0	Physical and Chemical Properties -
<u>HMIS</u>	Health hazards 2	Flammability 3	Physical hazards 0	Personal protection X

Key to Classifications and Hazard Statements contained in Sections 2 and 3

Flam. Aerosol 1 (H222): Extremely flammable aerosol; Flammable Aerosols, Cat 1 (H229) - Pressurized gas; May burst if heated
 Asp. Tox. 1 (H304): May be fatal if swallowed and enters airways; Aspiration, Cat 1
 Skin Irrit. 2 (H316): Causes mild skin irritation; Skin Corr/Irritation, Cat 2
 STOT SE 3 (H336): May cause drowsiness or dizziness; Target Organ Single, Narcotic, Cat 3
 Aquatic Chronic 1 (H410): Very toxic to aquatic life with long lasting effects; Chronic Env. Tox., Cat 1
 Skin Irrit. 2 (H315): Causes skin irritation; Skin Corr/Irritation, Cat 2
 Aquatic Acute 1 (H400): Very toxic to aquatic life; Acute Env. Tox., Cat 1
 Flam. Liq. 2 (H225): Highly flammable liquid and vapor; Flammable Liquid, Cat 2
 EUH066: Repeated exposure may cause skin dryness or cracking
 Flam. Liq. 3 (H226): Flammable liquid and vapor; Flammable Liquid Cat 3
 Flam. Gas 1 (H220): Extremely flammable gas; Flammable gases, Cat 1
 Press. Gas (H280): Contains gas under pressure; Pressurized Gas, Compressed Gas
 Eye Irrit. 2 (H319): Causes serious eye irritation; Eye Dam Irrit., Cat 2
 [Asp. Tox. 2 (H305)]: May be harmful if swallowed and enters airways; Aspiration, Cat 2

Issue Date 1992 11 01

Revision Date 2016 05 11

Revision No

SKUS EN

1992 11 01: Initial release.

1994 12 01: Modified to update component information.

1997 10 01: Modified to update component information.

1998 12 01: Modified to update component information.

1999 02 01: Modified to update component information.

2000 03 01: Modified to update component information.

2002 10 01: Modified to update transportation information.

2003 04 01: Modified to update health hazard information.

2006 04 04: Modified to conform to 16 part format of ANSI Standard Z400.1-2004.

2007 04 04: Modified to correct environmental and ecological hazards identifications.

2008 07 02: Modified to update regulatory information.

2013 03 16: Modified to update expiring issue date.

2015 06 12: Modified to conform to 29 CFR 1910 (OSHA HCS).

2015 06 12: Modified to conform to Regulation (EC) No. 1272/2008.

2016 05 11: Modified to update component information.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer warranty against patent infringement.

End of Safety Data Sheet