



“Technical Data Sheet”

Revision Date: 05/20/2013

Product Type:	Sunbrella® Sling Fabric
Fiber Content:	PVC Coated Polyester / Sunbrella® Acrylic

Test Name	Test Method	Basis	Nominal Value
Fabric Construction: Ends	ASTM D3775	Each	42
Fabric Construction: Picks	ASTM D3775	Each	Style Dependent
Fabric Weight	ASTM D3776	Ounces/Square Yard	13.5
Finished Fabric Width	ASTM D3774	Inches	54.0
Seam Slippage	ASTM 4034	Lbs. of Force	80 Warp 60 Filling
Break Strength	ASTM D5034	Lbs. of Force	300 Warp 300 Filling
Bow / Skew	ASTM D3882	Inches	1.0
Tear Strength	ASTM D2261	Lbs. of Force	40 Warp 40 Filling
Crocking	AATCC 8	Grade	5 Wet 5 Dry
Wyzenbeek Abrasion – Cotton Duck	ASTM D4157	Cycle	15,000 Warp 15,000 Filling
California Technical Bulletin #117	TB 117	Pass/Fail	CS 191-53 Class I Pass
UFAC Flammability	Interior Fabrics Test Method	Pass/Fail	Pass
Colorfastness to Light	ASTM G154-00 (QUV Test) - PVC	Grade	Grade 4 @ 1000 hrs.
	AATCC 169 Option 3 - Acrylic	Grade	Grade 4 @ 2200 kJ
	SAE J 2527 - Acrylic	Grade	Grade 4/5 @ 1500 kJ