


YKK®

YKK(USA)INC. MACON
PRODUCT DATA SHEET

ITEM LBRU 2"

DATE 06/2010

BUCKLE & NOTIONS



STRENGTH

	AVG KG	AVG LB
AVERAGE BREAK STRENGTH	171.60	378.30
SLIPPAGE (at break)	< 1"	

DIMENSIONS

	MM	INCH
A	81.20	3.20
B	60.80	2.39
C	50.70	2.00
D	15.15	0.60

MATERIAL & CONSTRUCTION

DELRIN
PLASTIC INJECTION

PROPERTIES

COLOR FASTENERS	WASH	AATCC - 5
	DRYCLEAN	AATCC - 5
	WEATHERING	AATCC - 4 - 5 @ 100 Hrs.
MELTING POINT (° F)	347 ° F	
DECOMPOSITION TEMPERATURE	Do not maintain above 400°F for more than 30 min.	
CHEMICAL RESISTANCE	SOLVENTS	Excellent resistance to a wide variety
	ACIDS/ALKALI	Not recommended outside the pH range of 4 ~ 9
	STERILIZATION	Pressurized Steam
STERILIZATION	Ethylene Oxide	Excellent
	Gamma Radiation	Compatible up to 1 Mrad
	IMPACT (NOTCHED IZOD)	-40 (° F)
73 (° F)		1.4 FT-LB/IN
FLAMMABILITY (FMVSS 302)	AVG 1.9 INCH/MIN	
U.L. APPROVAL FOR PFD	YES	Usage Codes: 2,2F,3,3F,4H,5H,5R,5WV

0100

NOTICE - DISCLAIMER

ANY INFORMATION CONTAINED HEREIN IS FOR THE SOLE PURPOSE OF PROVIDING PURCHASER WITH GENERAL KNOWLEDGE ABOUT YKK PRODUCTS, YKK DOES NOT MAKE ANY WARRANTY OF ANY KIND, NEITHER EXPRESS OR IMPLIED, AS TO THE PRODUCTS, PRODUCT PRICES OR OTHERWISE.